






UNISTRUT
MIDWEST

Spanware® Sanitary IMP-Anchors

The Spanware® Sanitary IMP-Anchor system is designed specifically for attaching Food Grade Strut and other industrial components to insulated metal panels.

	Application 1 <i>Cantilevered stud</i>	Application 2 <i>Cantilevered stud with Food Grade Strut</i>	Application 3 <i>Pair of studs coupled vertically</i>
			
	<ul style="list-style-type: none"> • Restraint factor approaching zero • Static loading @1g • Allowable downward shear force parallel to wall and within 1.2" of wall plane 	<ul style="list-style-type: none"> • Restraint factor approaching zero • Static loading @1g • Downward shear force parallel to wall and within 2.82" of wall plane 	<ul style="list-style-type: none"> • Restraint factor approaching one • Static loading @1g
ANCHOR			
IMP-AD-375-S	■	+	See chart 1 below
IMP-AD-250-S	■	+	See chart 1 below
IMP-AD-210-S	■	+	See chart 1 below
IMP-AD-375	○	◆	See chart 2 below
IMP-AD-250	○	◆	See chart 2 below
IMP-AD-210	○	◆	See chart 2 below
IMP-AS-375	○	◆	See chart 3 below
IMP-HDT-375			See chart 4* below
	■ rated for 17 lbs ○ rated for 35 lbs	+ rated for 12 lbs ◆ rated for 25 lbs	

Safe Working Load Charts

Application 3 shown in lbs



www.Unistrut.biz
Sales@unistrut.biz
(800) 586-4787

Anchor center distance "L"	① Offset Distance from wall "D"				Anchor center distance "L"	③ Offset Distance from wall "D"			
	3"	4"	5"	6"		3"	4"	5"	6"
6"	20	15	12	7	6"	40	30	25	15
9"	25	22	20	10	9"	55	50	40	20
12"	30	25	22	20	12"	65	55	50	40
24"+	35	30	27	25	24"+	80	70	60	50

Anchor center distance "L"	② Offset Distance from wall "D"				Anchor center distance "L"	④* Offset Distance from wall "D"			
	3"	4"	5"	6"		3"	4"	5"	6"
6"	40	30	25	15	6"	60	45	30	20
9"	50	45	40	20	9"	80	55	40	30
12"	60	50	45	40	12"	100	80	55	45
24"+	70	60	55	50	24"+	120	100	80	60

*The working loads shown above use a combination of anchors: IMP-HDT-375 upper + IMP-AS-375 lower.